

Chapter 7A compliant: Tested and listed to ASTM2886.
OSFM BML listing: 8165-2192, ICC-ESL listing: 1300

1 Hour Fire Rated, ICC-ESL listing: 1299. **Canadian Compliance** : ICC-ESL: 1455 [CAN/ULC-S101-14]

WWW.VULCANVENTS.COM

(916) 652-7424

info@vulcanvents.com

P.O. Box 1126 Loomis, CA. 95650





1299,1300,1455



Required Installation:

Use EverKem 814+ intumescent firestop caulking or similar, along flanges.

For application details and installation examples, please visit www.VulcanVents.com



VFS414FB PRODUCT SPECIFICATION & DATA SHEET

Proudly Manufactured By:



www.newcalmetals.com

Model Description
Model Number
Model Size

Foundation/Soffit Vent
VFS414FB
13-1/2" x 3-1/2"

Flange Type
NFVA

Foam Back
24 sq. in.

Frame & Flange
Intumescent Core
Ember Mesh
Pest Screen

G90 Galvanized Steel - 26GA

5mm Hexagonal Matrix - Aluminum with intumescent coating

14 Mesh - 304 Stainless Steel (Faces interior)

Galvanized Steel Screen - 1/8" (Faces exterior)