

Chapter 7A compliant: Tested and listed to ASTM2886.
OSFM BML listing: 8165-2192, ICC-ESL listing: 1300

1 Hour Fire Rated, ICC-ESL listing: 1299. **Canadian Compliance** : ICC-ESL: 1455 [CAN/ULC-S101-14]

WWW.VULCANVENTS.COM

(916) 652-7424

info@vulcanvents.com

P.O. Box 1126 Loomis, CA. 95650




1299,1300,1455




Recommended Installation:

Use EverKem 814+ intumescent firestop caulking or similar, along flanges.


For application details and installation examples, please visit www.VulcanVents.com




TOP VIEW




ISOMETRIC VIEW



Intumescent Core



FRONT VIEW



SIDE VIEW

VFS414S PRODUCT SPECIFICATION & DATA SHEET

Proudly Manufactured By:  **NEW CAL**
METALS INC.

www.newcalmetals.com

Model Description | **Foundation Vent**
Model Number | **VFS414S**
Model Size | **13-1/2" x 3-1/2"**

Flange Type | **Stucco**
NFVA | **24 sq. in.**

Frame & Flange
Intumescent Core
Ember Mesh

G90 Galvanized Steel - 26GA
5mm Hexagonal Matrix - Aluminum with intumescent coating
14 Mesh - 304 Stainless Steel

